

SERIES GSA SWD POWER SUPPLY (Single Phase) 5,12 & 48 VOLT DC OUTPUT

**DIN RAIL MOUNT
COMPACT SIZE
REGULATED OUTPUT**

5 & 10 Amp



FEATURES

Single phase input
Wide Input Range 100-240VAC




SPECIFICATIONS

| | |
|--------------------|--|
| Input Voltage | 100 - 240 VAC |
| Frequency | 47 - 63 Hz |
| Output voltage | Select: 5VDC, 12VDC, 48VDC |
| Temperature rating | -10° + 50°C |
| Approvals | 02-UL1950, UL508 listed, Class 2, 05, 10, 20 - UL 508 Listed |
| Protection Type | Internal Fuse T2A / 250 VAC |
| Connection | 02-Quick Connect Terminals, 05,10 ,20 -Screw Clamp Terminals |

| Selection | GSA SWD 02/5 | GSA SWD 02/12 | GSA SWD 5/12 | GSA SWD 10/48 | GSA SWD 20/48 | | | | | | | |
|------------------------------|-------------------|-------------------|--------------------|--------------------|-------------------|--------------------|--------------------|-------------------|--------------------|--------------------|--------------------|--------------------|
| Catalog Number | D 0023 50 | D 0023 51 | D 0023 06 | D 0023 18 | D 0023 28 | | | | | | | |
| List Each | \$80.00 | \$80.00 | \$120.00 | \$180.00 | \$300.00 | | | | | | | |
| Output Voltage | 5VDC | 12VDC | 12VDC | 48VDC | 48VDC | | | | | | | |
| Output Current | 10 A | 5A | 10A | 5A | 10A | | | | | | | |
| Noise in mV | 50 | 50 | 100 | 100 | 100 | | | | | | | |
| Dimensions approx. mm (Inch) | H 90 (3.5") | W 40 (1.6") | D 115 (4.5") | H 125 (4.9") | W 63 (2.5") | D 126 (5.0") | H 125 (4.9") | W 83 (3.3") | D 126 (5.0") | H 125 (4.9") | W 175 (6.9") | D 116 (4.6") |



**Din Rail Mount
SWD**



**Dimensions
Approx.**