

SERIES GSA SWD POWER SUPPLY (Single Phase) 24 VOLT DC OUTPUT

DIN RAIL MOUNT **1.25 Amp to 20 Amp**
COMPACT SIZE **30 Watt to 480 Watt**
REGULATED OUTPUT



| FEATURES | |
|------------------------------|---|
| Single phase input | UL cULus CE |
| Wide Input Range 100-240 VAC | |
| SPECIFICATIONS | |
| Input Voltage | 100 - 240 VAC |
| Frequency | 47 - 63 Hz |
| Output voltage | Select: 24 VDC |
| Output voltage adj. | -5 +15% |
| Temperature rating | -10°C + 50°C |
| Approvals | 01, 02 - UL1950, UL508 Listed, Class 2 05, 10, 20 - UL508 Listed |
| Protection | Internal Fuse T2A / 250VAC |
| Connection | 01, 02 Quick Connect Terminals 05, 10, 20 Screw Clamp Terminal |

| Selection | GSA SWD 01 | GSA SWD 02 | GSA SWD 05 | GSA SWD 10 | GSA SWD 20 |
|----------------------------|--|--|---|---|--|
| Catalog Number | D 0023 01 | D 0023 02 | D 0023 05 | D 0023 10 | D 0023 20 |
| List Each | \$65 | \$70 | \$110 | \$150 | \$305 |
| Output Voltage | <u>24VDC</u> | <u>24VDC</u> | <u>24VDC</u> | <u>24VDC</u> | <u>24VDC</u> |
| Output Current | 1.25A | 2.5A | 5A | 10A | 20A |
| Noise in mV | 50 | 50 | 50 | 100 | 100 |
| Dimensions approx. mm Inch | H W D 90 40 115 (3.5") (1.6") (4.5") | H W D 90 40 115 (3.5") (1.6") (4.5") | H W D 125 63 126 (4.9") (2.5") (5.0") | H W D 125 83 126 (4.9") (3.3") (5.0") | H W D 125 175 116 (4.9") (6.9") (4.6") |

DETAS
POWER SUPPLIES



**Din
Rail Mount**

