

ON-OFF DISCONNECTS



S4 ENCLOSURE



S4 ENCLOSURE
IP55 NON-METAL



NEMA 4X

ON-OFF	SIZE	rated current Ith A	current UL/CSA (INDUCTIVE)	WITH BE OPERATOR		WITH D OPERATOR			WITH BY OPERATOR	
				CATALOG NUMBER	LIST PRICE	CATALOG NUMBER	LIST PRICE	Type of S4 enclosure	CATALOG NUMBER	LIST PRICE
3-pole	D05	16	16	E D05-3BE-M1-*	\$109	E D05-3D-S4-*	\$98	T8/2	E D05-3BY-4X-*	\$158
	D1	25	25	E D1-3BE-M1-*	115	E D1-3D-S4-*	104	T8/2	E D1-3BY-4X-*	164
	D2	32	40	E D2-3BE-M1-*	165	E D2-3D-S4-*	168	T5/6	E D2-3BY-4X-*	237
	D3	50	63	E D3-3BE-M1-*	207	E D3-3D-S4-*	219	T5/6	E D3-3BY-4X-*	273
	D4	100	100	E D4-3BE-M1-*	290	E D4-3D-4X-*	297	H362	E D4-3BY-4X-*	365
	D5	125	125	E D5-3BE-M1-*	382	E D5-3D-4X-*	419	AM1206RL	E D5-3BY-4X-*	438
	D6	160	200	-	-	E D6-3D-4X-*	1021	AM2068RL	-	-
	D7	250	250	-	-	E D7-3D-4X-*	1600	AM2068RL	-	-
	DL8	400	-	-	-	For "BE" handle change "3D" to 3BE" (same price)	-	-	-	-
DL9	630	-	-	-	-	-	-	-	-	
4-pole	D05	16	16	E D05-4BE-M1-*	\$115	E D05-4D-S4-*	\$129	METAL ENCLOSED 3 POLE TO ORDER For Nema 12 replace 4X in the 3 pole part # with M12 respectively. Add the following list prices: ED05 \$10.00 List Adder ED1 \$10.00 ED2 \$15.00 ED3 \$15.00 ED4 \$20.00 ED5 \$20.00 ED6 \$30.00 ED7 \$30.00 P/N Example: Change E D1-3BY-4X-* to E D1-3BY- M12-* \$174 List 2 Pole (Size D1 Only) Deduct \$10 from List Price P/N Example: Change 3 to 2 E D1-2BE (2 pole)		
	D1	25	25	E D1-4BE-M1-*	121	E D1-4D-S4-*	135			
	D2	32	40	E D2-4BE-M1-*	180	E D2-4D-S4-*	183			
	D3	50	63	E D3-4BE-M1-*	222	E D3-4D-S4-*	234			
	D4	100	100	E D4-4BE-M1-*	317	E D4-4D-4X-*	324			
	D5	125	125	E D5-4BE-M1-*	409	E D5-4D-4X-*	446			
	D6	160	200	-	-	E D6-4D-4X-*	1111			
	D7	250	250	-	-	E D7-4D-4X-*	1690			
	DL8	400	-	-	-	-	-			
DL9	630	-	-	-	-	-				
6-pole	D05	16	16	E D05-6BE-M1-*	\$133	E D05-6D-4X-*	\$158			
	D1	25	25	E D1-6BE-M1-*	139	E D1-6D-4X-*	164			
	D2	32	35	E D2-6BE-M1-*	401	E D2-6D-4X-*	474			
	D3	63	50	E D3-6BE-M1-*	474	E D3-6D-4X-*	547			
	D4	80	60	E D4-6BE-M1-*	729	E D4-6D-4X-*	784			
	D5	125	100	E D5-6BE-M1-*	875	E D5-6D-4X-*	930			
	D6	150	100	-	-	E D6-6D-4X-*	2188			

DISCONNECTS
to 600 AMPS

***SUFFIX: Add - RG for Red-Yellow operator handle
Add -SS for Black handle "D" type only
Add -SI for Black-Silver operator "BE" handle**

◆ NEMA 4X enclosure is UL/CSA per NEMA requirements.
Operator handle type BY is IP 67. Types BE & D are IP65.

DIMENSIONS: See page 204

**For "BY" Type Defeatable Operator, replace
"BE" with "BY" - Add \$10 List**